

DECLARATION OF PERFORMANCE

Nr. 07-400

1. Identification	UREASPRAY 400 - hotsprayed 2-component polyurea coating
2. Product traceability	Productidentification and batchnumber on label on packaging
3. Use	Elastic waterproof polyurea coating
4. Name and address producer	ADCOS NV Ambachtsstraat 15 2390 Malle
5. System level	2+
6. Name and contact address of the authorised representative	Not applicable
7. Notified body	The organisation BCCA has done the initial inspection of the production unit and production- and quality control system at producers plant under level 2+. BCCA will continue the evaluation of the factory production control system.

8. Technical properties

Property	Result	European Norm
Tensile strength (EN 12311-2)	21 MPa	EN 12311-2
Hardness (EN ISO868)	48 (Shore D)	EN 1504-2
Adhesion to concrete (EN 1542)	3,725 N/mm ² (dry)	
	3,55 N/mm ² (wet)	
Crack bridging ability (EN 1062-7)	> 9 mm	
Elongation at break (EN 12311-2)	Min. 340 %	
Permeability to water vapour (EN ISO 7783)	< 2,5 g/m ² /dag	
Abrasion resistance (EN ISO 7784-2)	< 26 mg CS-10	
Capillary absorption (EN 1062-3)	< 13 mg/m ² ,h ^{0,5}	

9. The object of the declaration described above is in conformity with the relevant harmonisation legislation. This declaration of conformity is issued under the sole responsibility of the producer.

date: 2.10.2018

signed:

Johan Devroe
Managing Director