Adcos NV Italiëlei 189 bus 2 B-2000 Antwerpen Belgium



Tel +32 (0)3 385 38 50 Fax +32 (0)3 385 38 52 info@adcosgroup.com www.adcosgroup.com

Nr. 01-222 CCT 2C ELASTIC LV  ivery of the product is identified by the name: PURINJECT 2C ELASTIC by the batch number
ivery of the product is identified by the name: PURINJECT 2C ELASTIC by the batch number
y the batch number
products for ductile filling of cracks according to -5
IV Esstraat 15 alle icable
+
749 performed the ination of the product type on the basis of type testing (including ); spection of the manufacturing plant and of factory production ous surveillance, assessment and evaluation of factory production
וו ר



Tel +32 (0)3 385 38 50 Fax +32 (0)3 385 38 52 info@adcosgroup.com www.adcosgroup.com

8. Declared performance		
Essential characteristic	Performance	Harmonised technical specification
Adhesion and elongation capacity (EN 12618-1)	Adhesion: ca. 0,6 N/mm² (dry) ca. 0,6 N/mm² (wet) Elongation: > 10 %	
Watertightness (EN 14068)	Watertight at 2 x 10 <sup>5</sup> Pa	1
Glass transition temperature (EN 12614)	ca. 41,8 °C	
Injectability	Crack width: 0,3 mm	EN 1504-5
(EN 12618-2)	Moisture state: dry, damp and wet	
Durability (EN 12637-1)	Lost deformation work < 20 %	
Corrosion behaviour Deemed effect	Deemed to have no corrosive	
	effect	
Release of dangerous substances	Conform	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

date: 5-02,2018

100

signed:

Johan Devroe Managing Director