

PURTOP 1C is a 1-component aliphatic polyurethane topcoat for PURFLOOR 70.

APPLICATION

Ensures chemical resistance, as well as colour stability of surfaces exposed to UV radiation.

ADVANTAGES

- Cold applied system, easy application.
- Good wear and scratch resistance.
- Good chemical resistance.
- Easy to clean.
- Colour stable.

APPLICATION PRESCRIPTIONS

- **Preparation**
Thoroughly clean the surface to be treated in order to have a good adhesion. All dust, fat and loose particles are to be removed.
- **PURTOP 1C**
Apply PURTOP 1C with a roll. Do not use more than 120 g/m². Application of the topcoat must be within 72 hours of applying the PURFLOOR. After the topcoat is applied, avoid environmental factors like draft through windows or air-conditioning and major changes in temperature or humidity.

TECHNICAL DATA

| | |
|---------------------------------|---|
| Colour | Deliverable in most RAL colours |
| Density | ± 1,4 kg/litre, colour dependent |
| Flash point | > 100 °C |
| Minimum work temperature | 15°C underground temperature or 4°C above dew point |
| Maximum work temperature | 25°C underground temperature or 4°C below dew point |
| Tack free | On curing |
| Curing time | 12 to 16 hours, depending on temperature and humidity |
| Second layer | Wait minimum 16 hours |

PACKAGING

Standard packaging: 5 kg.

STORAGE

Store for 12 months in the original packaging. Keep the original packaging tightly closed to prevent contamination by humidity. Store in a dry place at a temperature between 10°C and 30°C.

SAFETY AND HEALTH PRECAUTIONS

Do not breathe dust/fume/gas/mist/vapours/spray.
 In case of inadequate ventilation wear respiratory protection.
 Wear protective gloves/clothing and eye/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower.
 For more information, consult the safety data sheet.