

Solvent free epoxy primer for epoxy coatings, epoxy floors and polyurethane floors.

DESCRIPTION

Solvent free epoxy primer used as a primer for epoxy coatings, epoxy floors and polyurethane self-levelling floors.

COMPOSITION

Solvent free pure epoxy primer.

PROPERTIES

- Low viscosity.
- Very good adhesion on concrete.
- High mechanical properties.

APPLICATION PRESCRIPTIONS

Mix A and B component intensely. Apply the mixture with a brush or roll on surface that needs treatment.

Non-cured product can be cleaned with acetone.

TECHNICAL DATA

Colour A component	Transparent yellow
Colour B component	Yellow
Pot life (20°C)	25-30 min
Mix proportion	2kg A / 1 kg B
Viscosity	520 mPa.s
Adhesion to concrete	> 2,5 N/mm ² (concrete failure)

PACKAGING

Sets of 3 or 6 kg. Other packaging on request.

STORAGE

In original packaging: 1 year. Store dry and cool.

SAFETY AND HEALTH PRECAUTIONS

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/clothing and eye/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower.

Read safety data (MSDS) for more information.